




MBR2050CT thru MBR2060CT

High Tjm Low IRRM Schottky Barrier Diodes



Dimensions TO-220AB



Dim.	Millimeter	
	Min.	Max.
A	12.70	13.97
B	14.73	16.00
C	9.91	10.66
∅D	3.54	4.08
E	5.85	6.85
F	2.54	3.18
G	1.15	1.65
H	2.79	5.84
J	0.64	1.01
K	2.45BSC	
L	5.05BSC	
M	4.32	4.82
N	1.14	1.39
Q	0.35	0.56
R	2.29	2.79

A=Anode, C=Cathode, TAB=Cathode

	V _{RRM}	V _{RMS}	V _{DC}
	V	V	V
MBR2050CT	50	35	50
MBR2060CT	60	42	60



Symbol	Characteristics	Maximum Ratings	Unit
I _(AV)	Maximum Average Forward Rectified Current @T _c =125°C	2X10	A
I _{FSM}	Peak Forward Surge Current 8.3ms Single Half-Sine-Wave Superimposed On Rated Load (JEDEC METHOD)	150	A
dv/dt	Voltage Rate Of Change (Rated V _R)	10000	V/us
V _F	Maximum Forward Voltage (Note 1)	I _F =10A @T _J =25°C 0.75 I _F =10A @T _J =125°C 0.65 I _F =20A @T _J =25°C 0.90 I _F =20A @T _J =125°C 0.80	V
I _R	Maximum DC Reverse Current At Rated DC Blocking Voltage	@T _J =25°C 0.1 @T _J =125°C 15	mA
R _{θJC}	Typical Thermal Resistance (Note 2)	2.0	°C/W
C _J	Typical Junction Capacitance Per Element (Note 3)	400	pF
T _J	Operating Temperature Range	-55 to +150	°C
T _{STG}	Storage Temperature Range	-55 to +175	°C

NOTES: 1. 300us Pulse Width, Duty Cycle 2%.
 2. Thermal Resistance Junction To Case.
 3. Measured At 1.0MHz And Applied Reverse Voltage of 4.0V DC.

FEATURES

- * Metal of silicon rectifier, majority carrier conducton
- * Guard ring for transient protection
- * Low power loss, high efficiency
- * High current capability, low V_F
- * High surge capacity
- * For use in low voltage, high frequency inverters, free whelling, and polarity protection applications
- * RoHS compliant

MECHANICAL DATA

- * Case: TO-220AB molded plastic
- * Polarity: As marked on the body
- * Weight: 2 grams
- * Mounting position: Any



MBR2050CT thru MBR2060CT

High T_{jm} Low IRRM Schottky Barrier Diodes




FIG. 1 - FORWARD CURRENT DERATING CURVE




FIG. 2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG. 3 - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL FORWARD CHARACTERISTICS





FIG. 5 - TYPICAL JUNCTION CAPACITANCE

MBR2050CT thru MBR2060CT

High Tjm Low IRRM Schottky Barrier Diodes

Marking



Ordering Information

Part Number	Package	Shipping	Marking Code
MBR2050CT	TO-220AB	50pcs / Tube	MBR2050CT
MBR2060CT	TO-220AB	50pcs / Tube	MBR2060CT